



NC455 Chassis Short Monitor

IL773 Specification Sheet

Tek-CARE®400 and Tek-CARE®400 P5 Nurse Call Systems • Rev. 2 - 11/2012

Features

- UL® 1069 Listed and cUL® Listed
- Mounts in a single-gang enclosure
- Test button
- Alarm LED and audible alarm
- Silence button

Description

The NC455 Chassis Short Monitoring Device monitors a single NC450 Central Equipment for any short circuit of 1M ohms or less between system power and chassis ground. The device has a test button as well as a tone silence button that silences the audible alarm without extinguishing the alarm LED.

Listings



UL® 1069 listed and cUL® listed to CSA C22.2 No. 205; UL® File Number E71599.



NC455 Chassis Short Monitor

Specifications

Dimensions: Height: 4.5" (114 mm)
 Width: 2.8" (71 mm)
 Depth: 1.45" (37 mm)
Mounting: Standard single-gang electrical box
Connections: Plug-in type

Required Components

Tek-CARE®400 or Tek-CARE®400 P5 nurse call system

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3

TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)