

SF301A, SF302 Call Cords

DESCRIPTION

The TekTone® SF301A (single) or SF302 (double) call cords are for use with the Tek-CARE® nurse call systems and wireless emergency call systems, where ¼" phono jacks are used. Ten-foot cords are also available as SF301A/10 and SF302/10. The SF301A and SF302 are oxygen safe call cords certified safe for use by all patients receiving oxygen therapy. These waterproof and impact resistant call cords have completely sealed push buttons.

LISTING

- SF301A is UL® 1069 and UL® 2560 Listed; SF302 is UL® 1069 Listed; UL® File Number E71599.

FEATURES

- One or two ¼" call cord jacks—push-button and geriatric call cords are available.
- Illuminated reset button.
- Dummy plugs available.
- Call-assurance LEDs for each call cord jack.
- UL/cUL® 1069 and UL® 2560 Listed.
- RoHS Compliant.



SF301A, SF302 Call Cords

SPECIFICATIONS

- Dimensions: 7' (2.13 m) long polyvinyl covered cord
- Construction: SPST-1A switch, Integral brass, fine silver contacts 1 AMP, 115 watt maximum, AC
- Connections: ¼" (6.35 mm) plug-in phono jack

REQUIRED COMPONENTS

- Tek-CARE®500 Wireless Nurse Call System with SF521UL or SF523UL Room Stations
- Tek-CARE®120 or 160 Nurse Call System with SF121 or SF122 Room Stations
- Tek-CARE®400 P5+ Nurse Call System with SF121 or SF123 Room Stations
- Tek-CARE®300III Nurse Call System with SF380A Patient Stations
- Tek-CARE®NC200N or NC150N Nurse Call Systems with IR151B or IR152B Patient Stations
- Tek-CARE®NC110N Nurse Call System with SF100C or SF102 Patient Stations