



# SF350B Presence Station

## IL407 Specification Sheet

Tek-CARE®400 P5 & NC300II Nurse Call Systems • Rev. 11 - 11/2012

### Features

- UL® 1069 Listed
- Push button and green LED for nurse presence indication
- Push button and yellow LED for aide presence indication
- Automatic nurse follower transfer
- Flame retardant (UL® 94V-0) plastic faceplate

### Description

The SF350B Presence Station provides push button registration of nurse presence (green LED indication), or aide presence (yellow LED indication) at remote locations. The nurse/aide presence indicator unit can also be used to transfer nurse follower feature from room to room as nursing staff proceeds with rounds. Depressing the nurse presence registration button automatically transfers indication of all subsequent patient calls to the remote location of the nurse, as well as to the master station. Plug-in connectors provide for simple wiring.

### Specifications

Dimensions:	Height:	4.50"	(114 mm)
	Width:	2.75"	(70 mm)
	Depth:	1.50"	(38 mm)
	Projects:	0.4375"	(11 mm) from mounting surface
Construction:	Flame retardant (UL® 94V-0) plastic faceplate. Switches and electronic components are circuit board mounted.		
Connections:	Plug-in connectors.		
Housing:	Single gang ring (IH357) with square box (IH358), or exact equal.		



SF350B Presence Station

### Listings



UL® 1069 listed; UL® File Number E71599.

### Applicable Systems

Tek-CARE®400 P5 Nurse Call System  
Tek-CARE®NC300II Nurse Call System

[www.tektone.com](http://www.tektone.com)

277 Industrial Park Road • Franklin, NC 28734 • [tektone@tektone.net](mailto:tektone@tektone.net)

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3  
TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)